



Exterior Full Size Lightbar



ENFLB

Features

- Modules can be configured as single, dual or tricolor for maximum functionality
- Inboard modules are available in single color 6 or 9 LEDs, dual color 12 LEDs or tricolor 18 LEDs
- Corner modules are offered in single color 12 or 18 LEDs, dual color 24 LEDs or tricolor 30 LEDs

INPUT VOLTAGE RANGE 9-16 Vdc

NUMBER OF LEDS AND MAXIMUM CURRENT DRAW @ 12.8 VDC

Inboard Warning Modules 6 LED Single Color: <1.0 Amp; 9 LED Single Color: <1.5 Amp; 12 LED Dual Color: <1.0 Amp or 18 LED Tricolor: <1.0 Amp
Corner Modules 12 LED Single Color: <2.0 Amp; 18 LED Single Color: <3.0 Amp; 24 LED Dual Color: <2.0 Amp or 30 LED Tricolor: <2.0 Amp
Takedown 6 LED Single Color: <1.0 Amp
Alley 3 LED Single Color: <0.5 Amp

NUMBER OF LEDS AND MAXIMUM WATTAGE @ 12.8 VDC

Inboard Warning Modules 6 LED Single Color: <6.4 Watts; 9 LED Single Color: <9.6 Watts; 12 LED Dual Color: <6.4 Watts or 18 LED Tricolor: <6.4 Watts
Corner Modules 12 LED Single Color: <12.8 Watts; 18 LED Single Color: <19.2 Watts; 24 LED Dual Color: <12.8 Watts or 30 LED Tricolor: <12.8 Watts
Takedown 6 LED: <12.8 Watts
Alley 3 LED: <6.4 Watts

FLASH PATTERNS

Warning 66
Takedown/Alley 25
Arrow L/C/R 11

OPERATING TEMPERATURE -40° C to +65° C / -40° F to +149° F

DIMENSIONS

Lengths 2 Module: 24" (61 cm); 4 Module: 36" (91 cm); 5 Module: 42" (107 cm); 6 Module: 48" (122 cm); 7 Module: 54" (137 cm);
8 Module: 60" (152 cm) or 10 Module: 72" (183 cm)
Height All modules: 2.55" (6.5 cm)
Depth All modules: 12" (31 cm)

MOUNTS Standard hook kit mount with angle adjustment wedge
Headache rack mount

CERTIFICATIONS SAE J845/J595 Class 1 certified and California Title 13, Class B certified
ECE R65 Category T, Class 2 certified (red or blue) and EMC/ECE R10-4 certified

WARRANTY Five-year
