



XF FLUSH MOUNT LIGHT



XF Flush Mount Light

Single Colors	EXFS10001-{x}
Dual Colors	EXFS10002-{y}
Features:	Low profile design with advanced LED output
Light Sync:	Up to 24 lighthead (Sync 2)
Dimensions(l):	1.6" (4.06 cm)
Dimensions(h):	1.51" (3.84 cm)
Dimensions(d):	1.54" (3.91 cm)
Certifications:	SAE J595, ECE R65, ECE R10, CA Title 13, CISPR25

Replace (x) or (y) in the Order Number for Standard Color Selection

Single Colors (x)	A=  B=  R=  W= 
Dual Colors (y)	D=   E=   F=   J=   K=   M=   P=  

XF LIGHT DIMENSIONS / SPECIFICATIONS: ////////////////////////////////////

TECHNICAL SPECIFICATIONS				
	Input Voltage:		9-32Vdc	
	Average Power	9.7 Watts	Max Power	19.4 Watts
	12Vdc		24Vdc	
Dual Color Version Current Consumption	Peak Current	Average Current	Peak Current	Average Current
Red	0.6	0.3	0.3	0.15
Blue, Amber White, Green	0.8	0.4	0.4	0.2
Single Color Version Current Consumption	Peak Current	Average Current	Peak Current	Average Current
Red	1.2	0.6	0.6	0.3
Blue, Amber White, Green	1.6	0.8	0.8	0.4
LED Count		6		
Number of Flash Patterns		20		
Sync		Sync 2, Up to 24 lights bluePrint Compatible		
Operating Temperature		-40°C to +65°C		
IP Rating		IP67		
Certifications		SAE J595 Class1, CA Title 13 Class B ECE R65 XA2, XB2, XR2 (single color) ECE R65 XA1, XB1, XR1 (dual color) ECE R10, CISPR25 Class 3		

